



North American Headquarters  
 7966 NC 56 Hwy Louisburg, NC 27549  
 919.497.0010  
[www.palzivna.com](http://www.palzivna.com)

## Certificate of Compliance

Standard for Approval	ASTM D1056 2A1, C1, Z1 and Suffix M
Product Description	Vizion V4.0 STD (4.0 PCF)

Properties	Data	Standard Requirements	UOM	Status
Density	60.8	48 - 80	kg/m <sup>3</sup>	Pass
Compression Deflection 25%	142	57 - 187	kPa	Pass
Oven Aged Comp Defl. 25%	+2.8	+/- 30 max	%	Pass
Water Absorption	4.6	10 max	%	Pass
C1 Ozone Resistance	No Cracking	No Cracking	-	Pass
Flammability Suffix M (tested at 13mm)	49	100	mm/min	Pass (>0.25" thickness)
Compression Set 50%	10.2	25 (max)	%	Pass

Date of Compliance:	6/15/2016
---------------------	-----------

Palziv North America certifies that this product was inspected and tested in accordance with written standards, and that the results are correct at the time of inspection. Due to the nature of the product, results will vary over time.

Deviation required for 2A1 Compression Deflection @ 25% Change from 15 - 35 kPa to 57 - 187 kPa

Authorized by

A handwritten signature in black ink that reads "Joseph A Andolsen".

Joe Andolsen  
 Testing Manager  
 Palziv North America