



North American Headquarters
 7966 NC 56 Hwy Louisburg, NC 27549
 919.497.0010
www.palzivna.com

Certificate of Compliance

Standard for Approval	MS-AY-551 Grade 3
Product Description	Vizion V4.0 (4.0 PCF)

Properties	Data	Standard Requirements	UOM	Status
Density	3.90	2.9 - 4.99*	lb/ft ³	Dev. Req.
Tensile Strength	918	450 (min)	kPa	Pass
Elongation at Break	343	110 (min)	%	Pass
Compression Set	11.6	30 (max)	%	Pass
Tear Strength	5.77	2.6 (min)	kN/m	Pass
Load Deflection 25%	145	114.5-190.3*	kPa	Dev. Req.
Load Deflection 25%	21.0	16.6-27.6*	PSI	Dev. Req.
Stain Resistance	no staining	no staining	-	Pass
Water Absorption	0.029	0.5 (max)	kg/m ²	Pass
Dimensional Stability	-1.95	10	%	Pass
Flammability (0.5")	43	100 (max)	mm/min	Pass

Date of Compliance:	3-Mar-16
---------------------	----------

Palziv North America certifies that this product was inspected and tested in accordance with written standards, and that the results are correct at the time of inspection. Due to the nature of the product, results will vary over time. *Deviations for density to 2.9 - 4.99 and load deflection to 114.5 - 190.3 kPa (16.6 - 27.6 PSI).

Authorized by

A handwritten signature in black ink that reads "Joe Andolsen".

Joe Andolsen
 Testing Manager
 Palziv North America