



North American Headquarters  
 7966 NC 56 Hwy Louisburg, NC 27549  
 919.497.0010  
[www.palzivna.com](http://www.palzivna.com)

## Certificate of Compliance

Standard for Approval	MS-AY-551 Grade 4
Product Description	Vizion V6.0 STD 2-step (6.0 PCF)

Properties	Data	Standard Requirements	UOM	Status
Density	6.0 (nominal)	5.4-6.6	lb/ft <sup>3</sup>	Pass
Tensile Strength	1060	690 (min)	kPa	Pass
Elongation at Break	242	120 (min)	%	Pass
Compression Set	7.9	20 (max)	%	Pass
Tear Strength	5.79	3.7 (min)	kN/m	Pass
Load Deflection 25%	194	117-172	kPa	Dev. Req.*
Stain Resistance	No Staining	No Staining	-	Pass
Water Absorption	0.02**	0.5 (max)	kg/m <sup>2</sup>	Pass
Dimensional Stability	2.5	10 (max)	%	Pass
Burn Rate (0.5")	21	100 (max)	mm/min	Pass

Date of Compliance:	24-Mar-16
---------------------	-----------

Palziv North America certifies that this product was inspected and tested in accordance with written standards, and that the results are correct at the time of inspection. Due to the nature of the product, results will vary over time.

\*Deviation required from 117-172 kPa to 148-241 kPa.

\*\*Results from V4.0 STD. V6.0 STD presumed to pass based on these results.

Authorized by

A handwritten signature in black ink that reads "Joe Andolsen".

Joe Andolsen  
 Testing Manager  
 Palziv North America