



North American Headquarters
 7966 NC 56 Hwy Louisburg, NC 27549
 919.497.0010
www.palzivna.com

Certificate of Compliance

Standard for Approval		MS-AY-561 A Grade 0		
Product Description		Vizion V2.0 SEV (EVA)		
Physical Properties	Test Results	Standard Requirements	UOM	Status
Tensile Strength	334	250 (min)	kPa	Pass
Tear Strength	2.1	1.3 (min)	kN/m	Pass
Elongation (% to break)	272	250 (min)	%	Pass
Compressive Deflection 25%	52	25-60	kPa	Pass
Compression Set	21	55 (max)	%	Pass
Dimensional Stability	4.4	10 (max)	%	Pass
Stain Resistance	No Staining	No Staining	-	Pass
Water Absorption	2.49	10 (max)	%	Pass
Flammability (11.3mm)	46	100 (max)	mm/min	Pass (≥ 0.25 " thickness)
Odor	2-3	3 (max)	-	Pass
Low Temperature Flexibility	No Cracking	No Cracking	-	Pass
Date of Compliance:		4/26/2017		

Palziv North America certifies that this product was inspected and tested in accordance with written standards, and that the results are correct at the time of inspection. Due to the nature of the product, results will vary over time.

Authorized by

A handwritten signature in black ink that reads "Joseph M Andolsen".

Joe Andolsen
 Testing Manager
 Palziv North America