



North American Headquarters  
 7966 NC 56 Hwy Louisburg, NC 27549  
 919.497.0010  
[www.palzivna.com](http://www.palzivna.com)

## Certificate of Compliance

Standard for Approval		MS-AY-512A Type 4		
Product Description		Vizion V6.0 STD (6.0 PCF)		
Properties/Procedures	Data	Standard Requirements	UOM	Status
Density- ASTM D3575W	6.0 (nominal)	5.4 - 6.6	lb/ft <sup>3</sup>	Pass
Tensile Strength- ASTM D3575T	98	123 (min MD), 96 (min CMD)*	PSI	Deviation Required
Elongation- ASTM D3575T	264	142 (min MD), 100 (min CMD)*	%	Pass
Compressive Deflection at 25%- ASTM D3575D	27.4	9.5 - 24.4	PSI	Deviation Required
Compression Set- ASTM D3575B	19	22 (max)	%	Pass
Thermal Stability- ASTM D3575S	-2	-4 (max)	%	Pass
Water Absorption- ASTM D3575L	0.02**	0.4 (max)	kg/m <sup>2</sup>	Pass
Flammability- FMVSS302, tested at 0.5" thickness	23	100 (max)	mm/min	Pass, ≥0.25" thickness

Date of Compliance:	12/14/2018
---------------------	------------

Palziv North America certifies that this product was inspected and tested in accordance with written standards, and that the results are correct at the time of inspection. Due to the nature of the product, results will vary over time.

\*It should be noted that this specification and requirements are written for roll foam and that V6.0 STD is block foam.

\*\*Results for V4.0. V6.0 expected to have similar results.

Authorized by:

Joe Andolsen  
 Testing Manager  
 Palziv North America