



North American Headquarters  
7966 NC 56 Hwy Louisburg, NC 27549  
919.497.0010  
[www.palzivna.com](http://www.palzivna.com)

### FMVSS302 Testing

**Test Laboratory:** Palziv North America  
**Test Date:** 2/16/2017  
**Test Conducted By:** Joe Andolsen  
**Test Material:** V4.0 STD  
**Sample Size:** 255mm x 100mm x 11.7mm  
**Lab Temperature (°F):** 64-70  
**Lab R.H. (%):** 50-52

Specimen Number	Burn Direction	*Notes	Burn Distance (in.)	Burn Time (sec.)	Results (in/min)	Pass	Fail
1	N/A*	3	4.3	300	0.86	X	
2	N/A*	3	4.7	300	0.94	X	
3	N/A*	3	5.7	300	1.14	X	
4	N/A*	3	5.3	300	1.06	X	
5	N/A*	3	5.8	300	1.16	X	

- \*Notes:**
1. Specimen did not ignite.
  2. Specimen ignited but self extinguished before entering timing zone.
  3. Test was discontinued after 5 minutes.
  4. The (\*\*) denotes that specimens were not provided by the manufacturer or by NHTSA
  5. The specimen ignited but did not burn to the timing zone in 5 minutes.

**Remarks:** \*Material is non-directional

Palziv North America certifies that this product was inspected and tested in accordance with written standards, and that the results are correct at the time of inspection. Due to the nature of the product, results will vary over time.