




## Industry Compliance Vizion

Palziv North America  
7966 NC 56Hwy Louisburg, NC 27549  
919-497-0010

Standard for Approval	FORD ESF-M8G156-A
Product Description	Vizion 6pcf STD

Properties	PNA Data	Standard Requirements	UOM	Status
Density min.	90	86.5	Kg/m <sup>2</sup>	Pass
Tensile Strength min.	1000	690	kPa	Pass
Elongation min.	125	125	%	Pass
Tear Resistance min.	5.7	4.4	kN/m	Pass
Compression Deflection 25%	275 min	84-147	kPa	Req. deviation
Cell count		75		N/A
Water absorption	See remark	10	%	Req. deviation
Dimensional Stability	1	Max 2.5	%	Pass
Low temp. Flex	No crack	No crack		Pass
Solvent resistance	No tackiness	No tackiness		Pass

Water absorption - Max 1% by volume

Date of Compliance	06/25/2014	QA Manager		Gil Cimering
--------------------	------------	------------	---	--------------

Data represents typical values tested in accordance with written standards.  
The information above on **Fuzion**® or **Vizion**® chemically cross-linked polyethylene foam is presented to the best of our knowledge.  
Results are measured by testing according to ASTM standards.

QCFV-IC-201