



North American Headquarters  
 7966 NC 56 Hwy Louisburg, NC 27549  
 919.497.0010  
[www.palzivna.com](http://www.palzivna.com)

## Certificate of Compliance

Standard for Approval	ESF-M8G156-B
Product Description	Vizion V4.0 STD (4.0 PCF)

Properties	Data	Standard	UOM	Status
3.5 Density	64 (nominal)	56.1	kg/m <sup>3</sup>	-
3.6 Cell Count Per Linear Inch	Not Tested	75 (min)	-	Not Tested
3.7 Hardness Durometer AA	Not Tested	20 +/- 5	AA	Not Tested
3.8 Load Deflection	146	48 - 110	kPa	Dev. Req.
3.9 Tensile Strength	683	552 (min)	kPa	Pass
3.10 Ultimate Elongation	306	100 (min)	kPa	Pass
3.11 Tear Resistance	3.82	2.6 (min)	kN/m	Pass
3.12 Dimensional Stability	Not Tested	+/- 2.5	%	Not Tested
3.13 Low Temperature Flexibility	No Cracking	No Cracking	-	Pass
3.14 Water Absorption, Static	Not Tested	10	%	Not Tested
3.15 Solvent Resistance	No Tackiness/Deterioration	No Tackiness/Deterioration	-	Pass

Date of Compliance:	4/12/2016
---------------------	-----------

Palziv North America certifies that this product was inspected and tested in accordance with written standards, and that the results are correct at the time of inspection. Due to the nature of the product, results will vary over time.

Authorized by

Joe Andolsen  
 Testing Manager  
 Palziv North America