



North American Headquarters
 7966 NC 56 Hwy Louisburg, NC 27549
 919.497.0010
www.palzivna.com

Certificate of Compliance

Standard for Approval		WSS-M99P48-A1		
Product Description		Vizion V4.0 STD (4.0 PCF)		
Properties	Result	Standard Requirements	UOM	Status
3.2.1 Odor Variant B* Condition 1	2	3 (max)	-	Pass
3.2.1 Odor Variant B* Condition 2	2			Pass
3.2.1 Odor Variant B* Condition 3	3			Pass
3.2.2 Fogging**	93	70 (min)	-	Pass
3.2.3 Flammability (tested at 13mm)	43	100 (max)	mm/min	Pass (≥ 0.25" thck)
3.2.4 Resistance to Mildew	No Mildew /Odor	No Mildew/Odor	-	Pass
3.2.5 Stress Cracking	N/A	No Cracking or Crazing	-	N/A
3.2.6 Accelerated Weathering Resistance	N/A	4 (min)	-	N/A
3.2.7 Corrosion**	No Galvanic Corrosion	No Galvanic Corrosion	-	Pass
3.3.1 Tensile Test	0.818	Report Only	MPa	Report Only
3.3.2 Density	4.33	Report Only	lb/ft ³	Report Only
3.3.3 Tear Resistance	3641	Report Only	N/m	Report Only
3.3.4 Constant Deflection Compression Set	54.7	Report Only	%	Report Only
3.3.4.1 Steam Autoclave Aging Exposure***	N/A	+/- 40% max from original value	%	N/A
3.3.4.2 Dry Heat Aging Exposure***	N/A	+/- 10% max from original value	%	N/A
3.3.5 Indentation Force Deflection	Not Tested	Report Only	N	Report Only
Date of Compliance:	12-Sep-16			

Palziv North America certifies that this product was inspected and tested in accordance with written standards, and that the results are correct at the time of inspection. Due to the nature of the product, results will vary over time.

*Variant B tested and passed requirement. Variant A passes on the assumption that the parts are smaller and produce less odor.

** Results for V2.0 STD. V4.0 STD expected to pass based on these results.

***Not applicable for x-linked PE foam

Authorized by

Joe Andolsen
 Testing Manager
 Palziv North America