



North American Headquarters  
 7966 NC 56 Hwy Louisburg, NC 27549  
 919.497.0010  
[www.palzivna.com](http://www.palzivna.com)

## Certificate of Compliance

Standard for Approval	GMW15063- Type 7
PNA Product Description	F3.0 STD (3.0 PCF)

Properties	Data	Standard Requirements	UOM	Status
Density	47.3	50 +/- 10	kg/m <sup>3</sup>	Pass
Compression Load Deflection 10%	28.0	> 20	kPa	Pass
Compression Load Deflection 25%	52.1	report	kPa	
Compression Load Deflection 50%	115	report	kPa	
Tensile Strength	415	report	kPa	
Elongation at Break	150	report	%	
Comp Set 25%, 1/2hr	39.0	report	%	
Comp Set 25%, 24hr	22	report	%	
Fogging/VOCs- GMW3235 Method B-Y1-T1	0.9	≤ 4	mg	Pass*
Flammability (as is)- GMW3232	36.3	< 100	mm/min	Pass
Flammability (aged)- GMW3232	Not Tested	< 100	mm/min	Not Tested
Interior Emissions- GMW15634	266	VOC ≤ 600 µg/g	µg/g	Pass*
Interior Emissions- GMW15634	202	SVOC ≤ 1000 µg/g	µg/g	Pass*
Resistance to Odor Wet Condition (Code A)- GMW3205	8.0	≥ 6	-	Pass*
Resistance to Odor Dry Condition (Code B)- GMW3205	4.0/5.0	≥ 6	-	Deviation Req.*
Mildew- GMW3259	Not Tested	No Mildew	-	Not Tested
Thickness	6.35-15.0	report	mm	**
Dimensional Stability- GMW4217	0.36	2.0 +/- 0.5	%	Pass

Date of Compliance:	1-Jun-15
---------------------	----------

Palziv North America certifies that this product was inspected and tested in accordance with written standards, and that the results are correct at the time of inspection. Due to the nature of the product, results will vary over time.

\*Test data taken from F2.0 STD tested by FILK Laboratory.

\*\*Tested thickness.

Authorized by

Joe Andolsen  
 Quality Manager  
 Palziv North America